

PREMIUM RESIN TECH.

RDR-1812

RDR-1812

Section 1 - Chemical Product and Company IdentificationProduct/Chemical Name: **RDR-1812**Manufacturer: **PREMIUM RESIN TECH.**3605- 32nd Street, Port Huron, Michigan 48060 (586) 530-3633

Chemical /Formula / Family: Epoxy Resin Bisphenol-A

Section 2- Hazards Identification**☆☆☆☆☆ Emergency Overview ☆☆☆☆☆****Potential Health Effects**

GHS LABEL :

HMIS		
H	1	PPE [†]
F	1	[†] Sec. 8
R	0	

Signal Word : "Warning"

Primary Entry Route: SKIN**Inhalation:** PRODUCT MAY CAUSE IRRITATION TO THE NOSE, THROAT AND RESPIRATORY TRACT.**Eye:** MAY BE MODERATELY IRRITATING TO THE EYES.**Skin:** MAY BE MODERATELY IRRITATING TO THE SKIN; MAY CAUSE SKIN SENSITIZATION. PROLONGED OR REPEATING LIQUID CONTACT CAN RESULT IN DEFEATING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS.**Ingestion:** PRODUCT IS MODERATELY TOXIC AND MAY BE HARMFUL IF SWALLOWED.**Carcinogenicity:** IARC, NTP, AND OSHA DO NOT LIST RDR-1812-C AS A CARCINOGEN.**Medical conditions aggravated by long-term exposure:** PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PREEXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT.**Chronic Effects:****Section 3 - Composition / Information on Ingredients**

Ingredient Name	CAS Number	% wt or % vol
EPOXY RESIN	25068-38-6	15-30
EPOXIDIZED NOVOLAC	28064-14-4	15-30
PIGMENT	113-86-4	2-5
THICKENER	7631-86-9	05-10
CALCIUM CARBONATE	1317-65-3	10-15
MILLED CARBON FIBER		5-15

Section 4 - First Aid Measures**Inhalation:** REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT, GIVE ARTIFICIAL RESPIRATION. IF NOT BREATHING. GET MEDICAL ATTENTION.**Eye Contact:** FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.**Skin Contact:** REMOVE CONTAMINATED CLOTHING/SHOES AND WIPE EXCESS FROM SKIN. FLUSH SKIN WITH WATER. FOLLOW BY WASHING WITH SOAP AND WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL CLEANED. CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES, CANNOT BE DECONTAMINATED AND SHOULD BE DESTROYED TO PREVENT REUSE.**Ingestion:** DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR VERY DROWSY. OTHERWISE, GIVE NO

MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING 30CC {2 TABLESPOONS} SYRUP OF IPECAC. IF IPECAC IS UNAVAILABLE, GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING FINGER TO BACK OF VICTIM'S THROAT. KEEP VICTIM'S HEAD BELOW HIPS WHILE VOMITING. GET MEDICAL ATTENTION.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: IF VICTIM IS A CHILD, GIVE NO MORE THAN 1 GLASS OF WATER AND 15CC {1 TABLESPOON} SYRUP OF IPECAC. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED FOLLOWING INCUBATION WITH A CUFFED ENDOTRACHEAL TUBE.

Special Precautions / Procedures: STORE IN COOL, DRY PLACE WITH ADEQUATE ENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES. HEATING THIS RESIN ABOVE 300°F IN THE PRESENCE OF AIR MAY CAUSE SLOW OXIDANT DECOMPOSITION ABOVE 500°F, POLYMERIZATION MAY OCCUR. SOME CURING AGENTS, POLYAMINES CAN PRODUCE EXOTHERMIC REACTIONS, WHICH IN LARGE MASSES CAN CAUSE RUNAWAY POLYMERIZATION AND CHARRING TO THE REACTIONS. FUMES AND VAPORS FROM THESE THERMAL AND CHEMICAL DECOMPOSITION VARY WIDELY IN COMPOSITION AND TOXICITY. DO NOT BREATH FUMES.

Section 5 - Fire-Fighting Measures

Flash Point: 200°F (>93°C)

Flash Point Method: SETAFLASH

LEL: N/AV **UEL:** N/AV

Flammability Classification: MATERIAL WILL NOT BURN UNLESS PREHEATED.

Extinguishing Media: USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.


Unusual Fire or Explosion Hazards: NO UNUSUAL HAZARDS.

Hazardous Combustion Products: NO UNUSUAL HAZARDS.

Fire-Fighting Instructions: DO NOT RELEASE RUNOFF FROM FIRE CONTROL METHODS TO SEWERS OR WATERWAYS.

Fire-Fighting Equipment: WEAR FULL BUNKER GEAR INCLUDING HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS. BECAUSE FIRE MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS, WEAR A SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR POSITIVE-PRESSURE MODE.

NFPA



Section 6 - Accidental Release Measures

Spill /Leak Procedures: MAY BURN ALTHOUGH NOT READILY IGNITABLE.

Small Spills: TAKE UP WITH AN ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

Large Spills: DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE / SALVAGE MATERIAL; DISPOSE OF PROPERLY.

Containment: FOR LARGE SPILLS, DIKE FAR AHEAD OF LIQUID SPILL FOR LATER DISPOSAL. DO NOT RELEASE INTO SEWERS OR WATERWAYS.

Cleanup: FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE.

Regulatory Requirements: FOLLOW APPLICABLE OSHA REGULATIONS (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: MINIMIZE ALL CONTACT WITH MATERIAL. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, APPLYING COSMETICS OR USING TOILET FACILITIES.

Storage Requirements: STORE IN COOL, DRY PLACE WITH ADEQUATE VENTILATION.

Regulatory Requirements: NONE

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: PROVIDE GENERAL OR LOCAL EXHAUST VENTILATION SYSTEMS TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW OSHA PELs (SEC. 2). LOCAL EXHAUST VENTILATION IS PREFERRED BECAUSE IT PREVENTS CONTAMINANT DISPERSION INTO THE WORK AREA BY CONTROLLING IT AT ITS SOURCE.

Administrative Controls:

Respiratory Protection: SEEK PROFESSIONAL ADVICE PRIOR TO RESPIRATOR SELECTION AND USE. FOLLOW OSHA RESPIRATOR REGULATIONS (29 CFR 1910.134) AND, IF NECESSARY, WEAR A MSHA/NIOSH-APPROVED RESPIRATOR. SELECT RESPIRATOR BASED ON ITS SUITABILITY TO PROVIDE ADEQUATE WORKER PROTECTION FOR GIVEN WORKING CONDITIONS, LEVEL OF AIRBORNE CONTAMINATION, AND PRESENCE OF SUFFICIENT OXYGEN. FOR EMERGENCY OR NONROUTINE OPERATIONS (CLEANING SPILLS, REACTOR VESSELS, OR STORAGE TANKS), WEAR AN SCBA. *WARNING! AIR-PURIFYING RESPIRATORS DO NOT PROTECT WORKERS IN OXYGEN-DEFICIENT ATMOSPHERES.* IF RESPIRATORS ARE USED, OSHA REQUIRES A WRITTEN RESPIRATORY PROTECTION PROGRAM THAT INCLUDES AT LEAST: MEDICAL CERTIFICATION, TRAINING, FIT-TESTING, PERIODIC ENVIRONMENTAL MONITORING, MAINTENANCE, INSPECTION, CLEANING, AND CONVENIENT, SANITARY STORAGE AREAS.

Protective Clothing/Equipment: WEAR CHEMICALLY PROTECTIVE GLOVES, BOOTS, APRONS, AND GAUNTLETS TO PREVENT PROLONGED OR REPEATED SKIN CONTACT. WEAR PROTECTIVE EYEGLASSES OR CHEMICAL SAFETY GOGGLES, PER OSHA EYE- AND FACE-PROTECTION REGULATIONS (29 CFR 1910.133). CONTACT LENSES ARE NOT EYE PROTECTIVE DEVICES. APPROPRIATE EYE PROTECTION MUST BE WORN INSTEAD OF, OR IN CONJUNCTION WITH CONTACT LENSES.

Safety Stations: MAKE EMERGENCY EYEWASH STATIONS, SAFETY/QUICK-DRENCH SHOWERS, AND WASHING FACILITIES AVAILABLE IN WORK AREA.

Contaminated Equipment: SEPARATE CONTAMINATED WORK CLOTHES FROM STREET CLOTHES. LAUNDRY BEFORE REUSE. REMOVE THIS MATERIAL FROM YOUR SHOES AND CLEAN PERSONAL PROTECTIVE EQUIPMENT.

Comments: NEVER EAT, DRINK, OR SMOKE IN WORK AREAS. PRACTICE GOOD PERSONAL HYGIENE AFTER USING THIS MATERIAL, ESPECIALLY BEFORE EATING, DRINKING, SMOKING, USING THE TOILET, OR APPLYING COSMETICS.

Section 9 - Physical and Chemical Properties

Physical State: LIQUID PASTE

Vapor Pressure: .01mm Hg(@20°C)

Vapor Density (Air=1): HEAVIER

Water Solubility: PRACTICALLY
INSOLUBLE

Other Solubility:

Appearance and Odor: Black w/ Slight Odor

Density:

Specific Gravity (H₂O=1, at 24 °C):

Freezing/Melting Point:

Boiling Point:

Viscosity: PASTE

% Volatile: 0.5

Evaporation Rate:
SLOWER THAN BUTYL
ACETATE

Section 10 - Stability and Reactivity

Stability: RDR-1812-C IS STABLE AT ROOM TEMPERATURE IN CLOSED CONTAINERS UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

Polymerization: HAZARDOUS POLYMERIZATION CANNOT OCCUR.

Chemical Incompatibilities: STRONG LEWIS OR MINERAL ACIDS AND STRONG MINERAL AND ORGANIC BASE / ESPECIALLY PRIMARY AND SECONDARY ALIPHATIC AMINES.

Conditions to Avoid: AVOID HEAT, FLAME AND CONTACT WITH STRONG OXIDIZING AGENT.

Hazardous Decomposition Products: THERMAL OXIDATIVE DECOMPOSITION OF RDR-1812-C CAN PRODUCE CARBON MONOXIDE, ALDEHYDES AND ACIDS MAY BE FORMED DURING COMBUSTION.

Section 11- Toxicological Information

Toxicity Data:*

- Very low toxicity if swallowed.
- LD50 , Rat, >15,000 mg/kg

Section 13 - Disposal Considerations

Disposal: CONTACT YOUR SUPPLIER OR A LICENSED CONTRACTOR FOR DETAILED RECOMMENDATIONS. FOLLOW APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.

Disposal Regulatory Requirements:

Container Cleaning and Disposal:

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Epoxy Phenol

Novolac Resin

Shipping Symbols:

Hazard Class: 9

ID No.: UN 3082

Packing Group: III

Label:

Special Provisions (172.102):

Packaging Authorizations

a) **Exceptions:** 173

b) **Non-bulk Packaging:** 173

c) **Bulk Packaging:** 173

Quantity Limitations

a) **Passenger, Aircraft, or Railcar:**

b) **Cargo Aircraft Only:**

Vessel Stowage Requirements

a) **Vessel Stowage:**

b) **Other:**

Section 16 - Other Information

Prepared By: Premium Resin Tech

Revision Notes: 2-2019

Additional Hazard Rating Systems:

Disclaimer: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Premium Resin Tech knowledge, or obtained from sources believed by Premium Resin Tech. to be accurate, and Premium Resin Tech. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product, read its label.